



GFGV.EX26789 Foam Liquid Concentrates

[Page Bottom](#)

Foam Liquid Concentrates

[See General Information for Foam Liquid Concentrates](#)

GLOBAL FIRE SOLUTION PTE LTD

EX26789

No, 16 Penjuru Close
608612 SINGAPORE

GLOBALCHEM AFFF 1, nominal 1 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.
GLOBALCHEM AFFF 3, nominal 3 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.
GLOBALCHEM AFFF 6, nominal 6 percent Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon fuels only.
GLOBALCHEM AR-AFFF 3/3, nominal 3 percent Alcohol Resistance Aqueous Film Forming Foam, +35 F minimum storage and use temperature. Hydrocarbon Fuels at 3 percent and Polar fuels at 3 percent.

Foam concentrates for use with the following equipment.

GLOBALCHEM AFFF 1, 1 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

ANGUS FIRE LTD, Model UNI225-1/3, 2-1/2 in. size, set at 1, inlet pressure of 145 psi with 100 feet of 2-1/2 in. hose between inductor and ANGUS FIRE LTD, Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire Ltd, Model F225HU	2-1/2	80

GLOBALCHEM AFFF 3, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

ANGUS FIRE LTD, Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 145 psi with 100 feet of 2-1/2 in. hose between inductor and ANGUS FIRE LTD, Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure psi
Angus Fire Ltd, Model F225HU	2-1/2	80

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam, in	Inlet Pressure, psi	Back Pressure, psi
Angus Fire Ltd, Model IND-40	1-1/2	0.18	135	65

FIXED FOAM DISCHARGE OUTLETS

Description	Orifice Diam, in.	Inlet Pressure, psi
Angus Fire Ltd, Model TPS-50MKV	0.59	60

GLOBALCHEM AFFF 6, 6 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

ANGUS FIRE LTD, Model UNI225, 2-1/2 in. size, set at 6, inlet pressure of 145 psi with 100 feet of 2-1/2 in. hose between inductor and ANGUS FIRE LTD, Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure, psi
Angus Fire Ltd, Model F225HU	2-1/2	80

GLOBALCHEM AR-AFFF 3/3, 3 PERCENT

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

ANGUS FIRE LTD, Model UNI225, 2-1/2 in. size, set at 3, inlet pressure of 145 psi with 100 feet of 2-1/2 in. hose between inductor and ANGUS FIRE LTD, Model F225U nozzle.

NOZZLES

Description	Size In.	Inlet Pressure, psi
Angus Fire Ltd, Model F225HU	2-1/2	80

PROPORTIONERS - FIXED IN-LINE INDUCTORS

Description	Size In.	Orifice Diam, in	Inlet Pressure, psi	Back Pressure, psi
Angus Fire Ltd, Model IND-40	1-1/2	0.18	135	65

FIXED FOAM DISCHARGE OUTLETS

Description	Orifice Diam, in.	Inlet Pressure, psi
Angus Fire Ltd, Model TPS-50MKV	0.59	60

Where,

Fuel	Min Application Rate, gpm/ft ²
Alc (Alcohols)	0.16

Last Updated on 2017-02-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".